

## PAB-68/WS - 2way Speaker Cabinet



**This particularly attractive and efficient series of PA speaker systems is clearly designed for effective fixed installations, whether in restaurants and bars, hotels, for background PA applications at sport facilities, PA applications in adjoining rooms at discotheques or at conferences: these PAB speaker systems offer a perfect price-performance ratio and a high quality. Pair of high-quality PA speakers, 70 WMAX, 8 Ohm**

- 2-way speaker systems in an ABS cabinet which is both functional and at the same time of an attractive appearance, bass-reflex
- Polypropylene bass speaker and dome tweeter with horn front attachment (waveguide)
- High-quality crossover networks
- Very well-balanced and clear sound which also impresses with a genuine reproduction of voices and demanding music
- LED at the front for indicating the level
- Supplied with wall bracket

## Teknisk Data

Active/passive	: passive
Operating voltage	: -
Impedance	: 8 Ohm
Frequency range	: 55-22,000 Hz
Amplifier power	: -
Max. power	: -
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way
Bass speaker	: polypropylene bass speaker
Midrange speaker	: -
Tweeter	: dome tweeter
Number of speakers	: 2
Speaker size	:
Power rating	: 40 W
Peak music power output	: 70 W
Sensitivity	: 90 dB/W/m
Max. rated SPL	: 106 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Material (housing/cabinet)	: ABS plastic
Colour	: white
Mounting facility	: 2 x thread M6
Protected against ball rebound	: -
Protective class	: -
Admiss. ambient temp.	: 0-40 Å°C
Power supply	: -
Dimensions	: 210 x 350 x 200 mm
Width	: 210 mm
Height	: 350 mm
Depth	: 200 mm
Weight	: 3.9 kg
Inputs	: speaker screw terminal
Outputs	: -

Other features

: -